

BA-56EEXEN(T)X2 CEILING SPEAKER

Zones 1, 2

Full catalogue available on our website: www.inpratex.com

ACOUSTIC SIGNALLING DEVICES

ZONES 1, 2 (gas)



This Ex ceiling speaker has extensive certification qualifying it for use in nearly all corners of the world.

This variation of the product separately contains two loudspeaker elements, two transformers and two terminals in one Ex housing (A + B system).






EU-Type Examination Certificate

ITEM REFERENCES

Designation:	Item No.:
BA-56EEXeN(T)x2	3D0302

TECHNICAL SPECIFICATIONS

Marking:	 II 2G Ex db eb IIB+H ₂ T6 Gb
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +50°C
Housing:	Anodized aluminium, RAL 9010 (front)
Mounting:	3 screws
Ingress protection:	IP54
Weight:	3,1 kg
Termination:	e-chamber, 2x screw terminal
Rated (standard) / Max. Power	3 W / 2x3 W
Sound pressure level 1W/1m:	83 db
Sound pressure level rated power:	87 db
Freq. range:	150 - 20000 Hz
Effective freq. range:	190 - 15000 Hz
Dispersion (-6dB) 1kHz / 4kHz:	113° / 40°
Cable entries:	4xM20x1,5 plastic plugs



100V TRANSFORMER TAPPINGS

RED : YELLOW	3,0 W
RED : GREEN	1,5 W
RED : BLUE	0,75 W