

DOUBLE PUSHBUTTONS-EMERGENCY CONTROL STATION

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

4



CONTROL & CONNECTION EQUIPMENT

ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



ATEX-certified control panels equipped with 2 double pushbuttons and an emergency stop button, certified for use in hazardous areas, made of glass-fibre reinforced polyester for use in explosive atmospheres.



EU-Type Examination Certificate

ITEM REFERENCES

Designation:	Item No.:
2 Double Pushbutton 1NO+1NC (GREEN-RED) - Emergency Stop 2NC Plastic cable gland M25 (10-17mm)	3J0135
2 Double Pushbutton 1NO+1NC (GREEN-RED) - Emergency Stop 2NC Brass Cable Gland M25 (13,2-20,5mm)	3J0136
2 Double Pushbutton 1NO+1NC (GREEN-RED) - Emergency Stop 2NC Brass Cable Gland M25 (17-26mm)	3J0137
2 Double Pushbutton 1NO+1NC (GREEN-RED) - Emergency Stop 2NC Nickel-plated Brass Cable Gland M25 (13,2-20,5mm)	3J0138
2 Double Pushbutton 1NO+1NC (GREEN-RED) - Emergency Stop 2NC Nickel-plated Brass Cable Gland M25 (17-26mm)	3J0139

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex db eb IIC T6 Gb II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Material:	Glass fibre reinforced polyester (GRP)
Dimensions:	220x120x90mm
Cable entries:	1xM25x1,5

INTERNAL CONTACT MODULE



INTERNAL CONTACT MODULE			
			
Marking:	Ex II 2G Ex de IIC Gb Ex I M2 Ex de I Mb		
Certificate:	EU-Type Examination Certificate		
Operating temperature:	-55°C to +60°C		
Ingress protection:	IP20		
Nominal isolation voltage:	690 V		
Voltage range:			
400 V	400 V	110 V	24 V
Utilization categories:			
AC-12	AC-15	DC-13	DC-13
Current range:			
16 A	10 A	0,5 A	1 A