

GRP JUNCTION BOX 3 CABLE ENTRIES - 8 TERMINALS

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

4



CONTROL & CONNECTION EQUIPMENT


ATEX JUNCTION BOXES

ZONES 1, 2 (gas) & 21, 22 (dust)



GRP (glass-reinforced polyester) junction box, suitable for use within ATEX rated Ex e Increased Safety areas.

Equipped with 3 cable entries and 8 2,5mm² + 2 PE terminals.



ITEM REFERENCES

Designation:	Cable glands:	Item No.:
A21-E1-01106+8T2,5+3PM16	3 Plastic cable glands (4-9 mm)	5A1105

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex eb IIC T6 Gb II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Housing:	Glass Reinforced Polyester (GRP)
Dimensions:	122x120x90 mm
Operating temperature:	-20°C to +40°C
Rated voltage:	max. 500V
Rated current:	max. 15 A
Terminals:	8 x 2,5mm ² + 2 PE
Ingress protection:	IP65
Cable entries:	3xM16x1,5 plastic cable glands for non-armoured cable

