


MUSHROOM TYPE LATCHING PUSH BUTTON

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



Pushbutton panels equipped with a mushroom type latching pushbutton, made of glass-fibre reinforced polyester for use in explosive atmospheres.

Can be supplied with M20 cable glands for armoured or non-armoured cable.



ITEM REFERENCES	
Designation:	Item No.:
Mushroom type latching push button 1NO+1NC - M20 Plastic cable gland	3J0126
Mushroom type latching push button 2NC - M20 Plastic cable gland	3J0127
Mushroom type latching push button 2NO - M20 Plastic cable gland	3J0128
Mushroom type latching push button 1NO+1NC - M20 Brass Cable Gland	3J0129
Mushroom type latching push button 2NC - M20 Brass Cable Gland	3J0130
Mushroom type latching push button 2NO - M20 Brass Cable Gland	3J0131
Mushroom type latching push button 1NO+1NC - M20 Nickel-Plated Brass Cable Gland	3J0132
Mushroom type latching push button 2NC - M20 Nickel-Plated Brass Cable Gland	3J0133
Mushroom type latching push button 2NO - M20 Nickel-Plated Brass Cable Gland	3J0134

TECHNICAL SPECIFICATIONS	
Marking:	 II 2G Ex db eb IIC T6 Gb  II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Material:	Glass fibre reinforced polyester (GRP)
Colour:	Black
Cable entries:	1xM20x1,5

INTERNAL CONTACT MODULE	
	
Marking:	 II 2G Ex de IIC Gb  I M2 Ex de I Mb
Certificate:	EU-Type Examination Certificate
Operating temperature:	-55°C to +60°C
Ingress protection:	IP20
Nominal isolation voltage:	690 V
Voltage range:	
400 V	400 V
110 V	24 V
Utilization categories:	
AC-12	AC-15
DC-13	DC-13
Current range:	
16 A	10 A
0,5 A	1 A