

MUSHROOM TYPE MOMENTARY PUSH BUTTON

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



Pushbutton panels equipped with a mushroom type momentary pushbutton, made of glass-fibre reinforced polyester for use in explosive atmospheres.

Can be supplied with M20 cable glands for armoured or non-armoured cable.



EU-Type Examination Certificate

ITEM REFERENCES

Designation:	Item No.:
Mushroom type momentary push button 1NO+1NC - M20 Plastic cable gland	3J0117
Mushroom type momentary push button 2NC - M20 Plastic cable gland	3J0118
Mushroom type momentary push button 2NO - M20 Plastic cable gland	3J0119
Mushroom type momentary push button 1NO+1NC - M20 Brass Cable Gland	3J0120
Mushroom type momentary push button 2NC - M20 Brass Cable Gland	3J0121
Mushroom type momentary push button 2NO - M20 Brass Cable Gland	3J0122
Mushroom type momentary push button 1NO+1NC - M20 Nickel-Plated Brass Cable Gland	3J0123
Mushroom type momentary push button 2NC - M20 Nickel-Plated Brass Cable Gland	3J0124
Mushroom type momentary push button 2NO - M20 Nickel-Plated Brass Cable Gland	3J0125

TECHNICAL SPECIFICATIONS

Marking:	 II 2G Ex db eb IIC T6 Gb  II 2D Ex tb IIIC T80°C Db
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP65
Material:	Glass fibre reinforced polyester (GRP)
Colour:	Black
Cable entries:	1xM20x1,5

INTERNAL CONTACT MODULE



Marking:	 II 2G Ex de IIC Gb  I M2 Ex de I Mb		
Certificate:	EU-Type Examination Certificate		
Operating temperature:	-55°C to +60°C		
Ingress protection:	IP20		
Nominal isolation voltage:	690 V		
Voltage range:			
400 V	400 V	110 V	24 V
Utilization categories:			
AC-12	AC-15	DC-13	DC-13
Current range:			
16 A	10 A	0,5 A	1 A