

2-ELEMENT PENDANT STATIONS

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX CONTROL STATIONS

ZONES 1, 2 (gas) & 21, 22 (dust)



The ATEX XAWP pendant control stations are suitable for all types of industry and primarily used on cranes.

Configuration:

1 red pilot light 24-254V AC/DC (text to be precise)

1 green push button, 1 NO contact (text to be precised)



EU-Type Examination Certificate

4



CONTROL & CONNECTION EQUIPMENT

ITEM REFERENCES

Designation:	Use:	Zones:	Item No.:
2-element pendant station	Indoor/Outdoor	1,2,21,22	3J1010

TECHNICAL SPECIFICATIONS

Marking:	II 2G Ex db eb mb IIC T6 Gb II 2D Ex tb IIIC T85°C Db IP65	
Certificate:	EU-Type Examination Certificate	
Operating temperature:	-20°C to +60°C	
Ingress protection:	IP65 according to EN/IEC 60529	
Material:	Glass fibre reinforced polyester (GRP)	
Dimensions:	410x98x76 mm	
Features of the contact block:	Ith = 10 A; Ui = 415 V	
	AC	Ue = 380 V; Ie = 1,9 A o Ue = 240 V; Ie = 3 A o Ue = 120 V; Ie = 6 A
	DC	Ue = 250 V; Ie = 0,27 A o Ue = 125 V; Ie = 0,55 A o Ue = 24 V; Ie = 2,87 A
Features of the LED pilot light:	Rated voltage: 24...254 V AC/DC Maximal current: 2...10 mA	
Mechanical endurance:	Head: 5 million operations - Contact block: 1 million operations	
Cable entries:	For cable Ø 10 to Ø 22 mm	