EXPLOSION-PROOF RECHARGEABLE HAND LAMP SLE 16 LED SET

Zones 1, 2, 21, 22

Full catalogue available on our website: www.inpratex.com

ATEX FLASHLIGHTS

ZONES 1, 2 (gas) & 21, 22 (dust)



The microprocessor controlled, rechargeable hand lamp, model EX SLE 16 LED, made of impact-resistant, high-quality plastic was certified according to the directive 2014/34/EU and relevant EMC provisions and may be used in vehicles.

The EX SLE 16 LED can be operated in a permanent, blinking and pilot lamp function and used as a warning light.





Flexible lamp head.

4-stage charge level display.

Emergency light function, turns on in the event of a power failure.

Maintenance-free led gel rechargeable battery.


12V-24V charger included.



| ITEM REFERENCES | | |
|-------------------|-----------|--|
| Model: | Item No.: | |
| EX SLE 16 LED SET | 1E0303 | |

| TECHNICAL SPECIFICATIONS | | |
|----------------------------|---|--|
| Marking: | II 2G Ex ib IIC T4 Gb II 2D Ex ib IIIC T135°C Db | |
| Certificate: | EU-Type Examination Certificate | |
| Housing: | Plastic, shock-resistant | |
| Ingress protection: | IP64 | |
| Lamp: | Power LED (approx. 180 lm) | |
| Run time: | Approx. 5h | |
| Beam distance: | Approx. 170 m | |
| Pilot lamp: | LED 5 mm | |
| Operating time pilot lamp: | Approx. 75h | |
| Rechargeable battery: | Lead-gel rechargeable battery Maintenance-free | |
| Charging voltage: | 230V AC 50/60Hz, 12/24V DC | |
| Weight: | 1100 g | |
| Dimensions: | 104x245x120 mm | |
| Operating temperature: | -20°C to +40°C | |

Dimensions in mm



Dimensions Acculux EX SLE 15 LED Dimensions Acculux EX SLE 16 LED