## **ATEX PORTABLE LAMPS**

## **ZONES 1, 2 (gas) & 21, 22 (dust)**

ATEX LED work light, equipped with a large handle, made of antistatic polypropylene housing, stainless st. screws and maintenancefree tempered glas. One lamp for 24V-48V, for AC and DC, for 2p and 3p systems and the weight being as little as 5 kg. Furthermore, the lamp is waterproof and will float in the water.



- · Diffuser not from polycarbonate but from maintenance free hardened glass: never static electricity issues and shockproof.
- Durable appearance, no rust or colour change over time due to stainless steel bolts, nuts and other components.
- Environmental friendly and non toxic materials.
- · Long productcycle and replaceable components with one cable fits all, therefore a very economic solution as well.
- Easy to transport due to a large grip, also for gloved hands.
- Rounded edges, protecting surrounding workplace.
- · Stackable and maintenance free.







ITEM REFERENCES	
Designation:	Item No.:
Ultra3 10 (with 10 m. cable H07RN-F) - Plug not included	1B1501
Ultra3 30 (with 30 m. cable H07RN-F) - Plug not included	1B1502

TECHNICAL SPECIFICATIONS						
Marking:	II 2G Ex ib mb IIC T4 Gb II 2D Ex ib mb IIIC T135°C Db					
Certificate:	EU-Type Examination Certificate					
Operating temperature:	-20°C to +50°C					
Rated voltage:	24-48VAC/DC (0Hz to 60Hz)					
Power:	35W					
Light sources:	81 LEDs, 5000°K   4100 lm					
Housing:	Throughout antistatic polypropylene, metal frame, stainless steel bolts					
Lens:	Scratch and chemical resistant hardened glass					
Design:	Easy to handle, also with gloves on. Easy stackable to save space					
Dimensions:	388 x 319 x 147 mm					
Weight:	5 kg					
Ingress protection:	IP65 according to EN 60529					

	ACCESSORIES								
	Description:	Item No.:		Description:	Item No.:				
ಿ	Magnet set with 3 magnets for Ultra	1B150A		Protective film for Ultra	1B150D				
	Scaffolding hook with locking device	1B150B	1						
	Subframe for Ultra	1B150C	1	Tripod for Ultra stainless steel	1B150E				