

# XPP-5422GMA DUAL-LIGHT FLASHLIGHT WITH DUAL MAGNETS

Zones 0, 1, 2

Full catalogue available on our website: [www.inpratex.com](http://www.inpratex.com)

## ATEX FLASHLIGHTS

## ZONES 0, 1, 2 (gas) & Mines



This non-rechargeable Dual-Light flashlight with dual magnets is cETLus, ATEX, INMETRO and IECEx listed Intrinsically Safe Permissible.

It uses a CREE LED rated at 120 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 170 meters. A 120 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination. Additionally, both the flashlight and the floodlight can be turned on at the same time for maximum versatility.

Submersible up to 1 meter.



EU-Type Examination Certificate

The integrated magnets located in the base of the handle and the pocket clip, provide for almost limitless hands-free usage.



## ITEM REFERENCES

Model:	Item No.:
XPP-5422GMA	1E0602

## TECHNICAL SPECIFICATIONS

Marking: ATEX	I M1 Ex ia op is I Ma II 1G Ex ia op is IIC T3 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T3 Ga CLASS I ZONE 0 Ex ia IIC T3 Ga
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	IP67
Drop rating:	2m
LED:	LED technology
Run time:	Flashlight Runtime: 17.5 h   Floodlight Runtime: 17.5 h   Dual-Light Runtime: 4.5 h
Luminous flux:	Flashlight: 120lm   Floodlight: 120lm   Dual-Light: 240lm
Beam distance:	170 m
Power source:	3 x AA (not included)
Weight:	196 g
Dimensions:	46 mm (head diameter)   28x38 mm (handle dimensions)