

XPP-5452G DUAL-FUNCTION HEADLAMP

Zones 0, 1, 2

Full catalogue available on our website: www.inpratex.com

ATEX HEADLAMPS

ZONES 0, 1, 2 (gas)

This 3 AAA dual-function headlamp is cETLus, ATEX, IECEx, INMETRO and KOSHA listed Intrinsically Safe. The XPP-5452G headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat.

The top-mounted switch provides user-selectable high or low brightness spotlight operation. 3 AAA batteries (included)



ANSI IP-67 Dustproof / Waterproof with a 2 meter drop rating.

Adjustable ratchet tilt head.



EU-Type Examination Certificate

ITEM REFERENCES

Designation:	Item No.:
XPP-5452G	1E2501

TECHNICAL SPECIFICATIONS

Marking: ATEX	II 1G Ex ia op is IIC T4 Ga
Marking: NEC 500	CLASS I DIV 1 GRPS A-D T4 CLASS II & III GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T4 Ga CLASS I ZONE 0 Ex ia IIC T4 Ga
Certificate:	EU-Type Examination Certificate
Operating temperature:	-20°C to +40°C
Ingress protection:	ANSI IP-67 Dustproof / Waterproof
Case material:	Engineered Polymer. Body Color: IS Green
Light Source:	LED
Switch function:	Single Body Switch. High-brightness Spotlight, Low-brightness Spotlight
Run time:	High Runtime: 6 h Low Runtime: 19 h
Luminous flux:	High Lumens: 180 High Candela: 2180 cd Low Lumens: 90 Low Candela: 962 cd
Beam distance:	High Beam Distance: 93 m Medium Beam Distance: 62 m
Power source:	3 x AAA (included)
Weight:	99 g
Dimensions:	61 x 48 x 46 mm
Strap/Mount:	Elastic & Rubber Straps