NON-SPARKING TOOLS

1ZONES 1, 2 (gas) & 21, 22 (dust)

1/2" Non-sparking Socket Wrench Set (12 points), made of Copper-Beryllium (Cu-Be) or Aluminium-Bronze (Al-Bron) alloys, suitable for use in hazardous areas.

The Non-sparking tools that compose this set are certified by the BAM Certification Body, stating that the materials from which they are made are suitable for use in potentially explosive atmospheres, in zones 1 and/or 21 of all explosion groups (I, IIA, IIB and IIC).



- Non-sparking tools cannot reach the hardness of conventional tools. For this reason the use of non-sparking tools has to be carried out with special care, avoiding overstraining, heating, etc.
- To avoid damage being caused to both tool and fastener, it is necessary to always ensure that the correctly sized spanner/wrench/screwdriver is selected. Due to the reduced strength and wear resistance of non-sparking Alloys selecting the correctly sized tool becomes essential to avoid premature wear and early deterioration of the tool.
- The use of non-sparking tools must not be the only preventive measure in areas which the items are designed for. Other items, clothes or present material must also be adequate for non-sparking

COPPER-BERYLLIUM ALLOY					
Designation:	Item No.:	Designation:	Item No.:	Weight:	Item No.:
Socket wrench 1/2" - 10mm	11A74452	Socket wrench 1/2" - 19mm	11A74461		
Socket wrench 1/2" - 11mm	11A74453	Socket wrench 1/2" - 20mm	11A74462		
Socket wrench 1/2" - 12mm	11A74454	Socket wrench 1/2" - 21mm	11A74463		
Socket wrench 1/2" - 13mm	11A74455	Socket wrench 1/2" - 22mm	11A74464		
Socket wrench 1/2" - 14mm	11A74456	Socket wrench 1/2" - 23mm	11A74465		
Socket wrench 1/2" - 15mm	11A74457	Socket wrench 1/2" - 24mm	11A74466]	
Socket wrench 1/2" - 16mm	11A74458	Socket wrench 1/2" - 27mm	11A74469		
Socket wrench 1/2" - 17mm	11A74459	Socket wrench 1/2" - 30mm	11A74472	5,5 kg	11A74269
Socket wrench 1/2" - 18mm	11A74460	Socket wrench 1/2" - 32mm	11A74473		
L	niversal joint 80	mm	11A70372		
	Extension 125m	m	11A76490		
	Extension 250mm				
Speeder handle 390mm			11A72416		
Sliding T handle 250mm			11A70378	1	
Ratchet 250mm			11A70375		
Socket wrench 1/2" - 1/4"	11A74502	Socket wrench 1/2" - 3/4"	11A74511		
Socket wrench 1/2" - 5/16"	11A74503	Socket wrench 1/2" - 25/32"	11A74512		
Socket wrench 1/2" - 3/8"	11A74504	Socket wrench 1/2" - 13/16"	11A74513		
Socket wrench 1/2" - 7/16"	11A74505	Socket wrench 1/2" - 7/8"	11A74514		
Socket wrench 1/2" - 1/2"	11A74506	Socket wrench 1/2" - 15/16"	11A74515		
Socket wrench 1/2" - 9/16"	11A74507	Socket wrench 1/2" - 1"	11A74516		
Socket wrench 1/2" - 19/32"	11A74508	Socket wrench 1/2" - 1.1/16"	11A74517		
Socket wrench 1/2" - 5/8"	11A74509	Socket wrench 1/2" - 1.3/16"	11A77790	5,5 kg	11A35813
Socket wrench 1/2" - 11/16"	11A74510	Socket wrench 1/2" - 1.1/4"	11A74519		
Universal joint 80mm			11A70372		
Extension 125mm			11A76490		
Extension 250mm			11A70385		
Speeder handle 390mm			11A72416		
Sliding T handle 250mm			11A70378		
Ratchet 250mm			11A70375		

NON-SPARKING 1/2" SOCKET WRENCH SET - 24 PCS

Full catalogue available on our website: www.inpratex.com



ALUMINIUM-BRONZE ALLOY					
Designation: Item No.: Designation:		Designation:	Item No.:	Weight:	Item No.:
Socket wrench 1/2" - 10mm	11A74479	479 Socket wrench 1/2" - 19mm			
Socket wrench 1/2" - 11mm	cket wrench 1/2" - 11mm 11A74480 Socket wrench 1/2"		11A74489		
Socket wrench 1/2" - 12mm	11A74481	Socket wrench 1/2" - 21mm	11A74490		
Socket wrench 1/2" - 13mm	11A74482	Socket wrench 1/2" - 22mm	11A74491		
Socket wrench 1/2" - 14mm	11A74483	11A74483 Socket wrench 1/2" - 23mm			
Socket wrench 1/2" - 15mm	11A74484	Socket wrench 1/2" - 24mm	11A74493		
Socket wrench 1/2" - 16mm	11A74485	Socket wrench 1/2" - 27mm	11A74496		
Socket wrench 1/2" - 17mm	11A74486	Socket wrench 1/2" - 30mm	11A74499	5,5 kg	11A74270
Socket wrench 1/2" - 18mm	11A74487	Socket wrench 1/2" - 32mm	11A74500		
Ur	iversal joint 80	mm	11A71269		
ı	xtension 125m	m	11A76491		
	xtension 250m	m	11A71281		
Speeder handle 390mm			11A72417		
Sliding T handle 250mm			11A71274		
Ratchet 250mm			11A71272		
Socket wrench 1/2" - 1/4"	11A74520	Socket wrench 1/2" - 3/4"	11A74529		
Socket wrench 1/2" - 5/16"	11A74521	Socket wrench 1/2" - 25/32"	11A74530		
Socket wrench 1/2" - 3/8"	11A74522	Socket wrench 1/2" - 13/16"	11A74531		
Socket wrench 1/2" - 7/16"	11A74523	Socket wrench 1/2" - 7/8"	11A74532		
Socket wrench 1/2" - 1/2"	11A74524	Socket wrench 1/2" - 15/16"	11A74533		
Socket wrench 1/2" - 9/16"	11A74525	Socket wrench 1/2" - 1"	11A74534		
Socket wrench 1/2" - 19/32"	11A74526	Socket wrench 1/2" - 1.1/16"	11A74535		
Socket wrench 1/2" - 5/8"	11A74527	Socket wrench 1/2" - 1.3/16"	11A77791	5,5 kg	11A35822
Socket wrench 1/2" - 11/16"	11A74528	Socket wrench 1/2" - 1.1/4"	11A74537		
Universal joint 80mm			11A71269		
Extension 125mm			11A76491		
Extension 250mm			11A71281		
Speeder handle 390mm			11A72417		
Sliding T handle 250mm			11A71274		
Ratchet 250mm			11A71272		

	MATERIALS			
Copper-Berylium Alloy				
	Ве	1.8 % - 2 %		
Composition	Ni+Co	0.2 % - 1.2 %		
Composition:	Otros	<0.5 %		
	Resto	Cu		
Hardness:	283-365 Brinell			
Tensile Strength:	1250 N/mm²			
	Aluminium-Bronze Alloy			
	Al	10 % - 12 %		
	Ni	4 % - 6 %		
Composition:	Fe+Mn	<5.8 %		
	Otros	<0.5 %		
	Resto	Cu		
Hardness:	229-291 Brinell			
Tensile Strength:	800 N/mm ²			

NON-SPARKING 1/2" SOCKET WRENCH SET - 24 PCS

Full catalogue available on our website: www.inpratex.com

PROPERTIES AND FEATURES				
Property:	Aplication or benefits:			
Non-sparking	Appropriate for explosive potential environments.			
Non-magnetic safety	Essential for equipments that require complete non-magnetic safety.			
Corrosion resistant	Specially well suited for applications in corrosive environments like encountered in marine works or fire-fighting applications.			
Forged after casting	Provide higher mechanical properties and better finishing.			
Ergonomic designs	The use of bi-material anti-slippery handles, dipping anti-slippery handles, totally ergonomic designs make operations easier, more comfortable and master.			

CAUTION:

These tools are not classified as anti-static because they do conduct electricity. Do not use high copper content tools (>65%) in direct contact with acetylene due to the possible formation of explosive acetylide, specially in the presence of moisture.

DIFFE	DIFFERENCES AND HOW TO MAKE THE CORRECT CHOICE				
Concept:	COPPER-BERYLLIUM Cu-Be	ALUMINIUM-BRONZE Al-Bron			
Hardness:	283-365 Brinell.	229-291 Brinell.			
Magnetism:	Non ferrous substance in the composition makes it safer when non-magnetic applications are required.	Minimum ferrous component makes them not 100% non-magnetic, although its low magnetism make it appropiate for non critical non-magnetic applications.			
Durability:	Much higher due to the higher hardness and tensile strength. Higher efforts can be made.	Not as much as Cu-Be			
Price:	Higher price due to the special raw material used.	Significantly lower price.			

	MAIN APPLICATION FIELDS					
		Plastic manufacturing	Breweries	Air Forces		
		Pharmaceutical Industry	Alcohol processing industries	Navy		
	Oil Companies	Fireworks Industry	Distilleries	Weapon & ammunition fabrication		
Gas & oil pipe lines Cher		Chemical Industry	Fire-fighters	Aerospace industry		
	Power Stations Paper making Indus		Mines	Automobile Industry		
	Paint Manufacturing	Flour silos and mills	Defence	Etc.		

COPPER BERYLLIUM ALLOY

Non ferrous substance in the composition makes it safer when non-magnetic applications are required.

ALUMINIUM BRONZE ALLOY

 $Minimum \, ferrous \, component \, makes \, them \, not \, 100\% \, non-magnetic, \, although \, its \, low \, magnetism \, make \, it \, appropriate \, for \, non \, critical \, non-magnetic \, applications.$