


NON-SPARKING CURVED SLOGGING RING WRENCHES

Full catalogue available on our website: www.inpratex.com

NON-SPARKING TOOLS

ZONES 1, 2 (gas) & 21, 22 (dust)

Non-sparking curved slogging ring wrenches, made of Copper-Beryllium (Cu-Be) or Aluminium-Bronze (Al-Bron) alloys, suitable for use in potentially explosive atmospheres. These Non-sparking curved slogging ring wrenches are certified by the BAM Certification Body, stating that the materials from which they are made are suitable for use in potentially explosive atmospheres, in zones 1 and/ or 21 of all explosion groups (I, IIA, IIB and IIC).

MILIMETERS					
	Size:	Lenght:	Weight:	Alloy:	Item No.:
	24 mm	160 mm	300 gr	Copper-Beryllium	11A74137
				Aluminium-Bronze	11A74138
	27 mm	170 mm	420 gr	Copper-Beryllium	11A74139
				Aluminium-Bronze	11A74140
	30 mm	180 mm	500 gr	Copper-Beryllium	11A74141
				Aluminium-Bronze	11A74142
	32 mm	190 mm	520 gr	Copper-Beryllium	11A74143
				Aluminium-Bronze	11A74144
	36 mm	210 mm	800 gr	Copper-Beryllium	11A74145
				Aluminium-Bronze	11A74146
	41 mm	220 mm	1000 gr	Copper-Beryllium	11A74147
				Aluminium-Bronze	11A74148
	46 mm	240 mm	1200 gr	Copper-Beryllium	11A74149
				Aluminium-Bronze	11A74150
	50 mm	250 mm	1500 gr	Copper-Beryllium	11A74151
				Aluminium-Bronze	11A74152
	55 mm	270 mm	1800 gr	Copper-Beryllium	11A74153
				Aluminium-Bronze	11A74154
	60 mm	280 mm	2200 gr	Copper-Beryllium	11A74155
				Aluminium-Bronze	11A74156
	65 mm	300 mm	2400 gr	Copper-Beryllium	11A74157
				Aluminium-Bronze	11A74158
	70 mm	310 mm	2800 gr	Copper-Beryllium	11A74159
				Aluminium-Bronze	11A74160